

# QUICK START GUIDE

---



TM67C Drum Mower

# IMPORTANT

# READ

# BEFORE

# FIRST USE

# QUICK START GUIDE

---

## TM67C Drum Mower

**Note:** The TM67C drum mower is also known as Galfre FR/G 170. This is the original manufacturer's designation of the model number, while TM67C is the model for the unit branded as Ibex.

### STARTUP ESSENTIALS

- **DO NOT TRY TO HOVER THE DRUMS ABOVE THE GROUND WHILE MOWING.** The drums are meant to sit completely on the ground except while in transport mode.
- **DO NOT:** allow the lower discs to scalp the ground when driving forward. To avoid this, do the following:
  - Ensure that the skid discs of the mower are either parallel to the ground or raised slightly **up in the front**. This can be achieved by extending the tractor's top link.
  - Raise the 3 point hitch during mowing until the lower lift arm is **above level**, at an angle sloping slightly downward toward the drum unit. This will ensure that the arm does not contact the drum unit and force it downward into the ground.
  - Use the lower limit chain to prevent the 3 point hitch from drifting down and putting pressure on the drum unit. (See p. 18 of the owner's manual for more details).
- **DO:** run the mower at 540 RPM, starting at idle speed and gradually increasing the throttle. Running the mower at too slow of an RPM will make cutting less efficient and stress the machine and the tractor.
- **DO NOT:** turn on an electric PTO with the throttle at high speed, which will apply extreme torque to the PTO shaft. Damage to the shaft or

# QUICK START GUIDE

---

drive components may occur. If the engine stalls when turning on the PTO, keep turning it on until drums get up to speed.

- **DO:** replace blades regularly to ensure a sharp cut.
- Failing to heed these warnings **may cause damage** to the machine.
- The machine is shipped with oil in the gearboxes. **Double-check the oil level and top off before each use.** Use an extreme pressure (EP) gear oil near 90 weight (80w90 is a common type). See section 6.2 of the manual for details on lubrication.
- There is no drain plug for the 90 degree gearbox that is attached to the 3 point hitch frame. An oil suction pump is recommended to remove oil when changing it at the beginning of each season.
- Review the section of the manual that discusses how to switch the mower from mowing mode to transport mode and back (Section 4.3). The transport lock lever must be in place during transport and must be loose when in mowing position. The “fasten lever” must be tightened during transport mode and loosened slightly in mowing mode.