



TM73 Flail Mower



Flail Mowers by Del Morino



Tractor Tools Direct is proud to offer an exclusive line of commercial grade flail mowers. With four sizes ranging from 52" to 84" of cutting width, you are sure to find one to fit your compact or larger utility tractor. A flail mower is a superior implement for tough jobs like brush and pasture mowing. And flail mowers evenly distribute clippings, without clumps that kill the grass underneath. We've teamed up with Del Morino of Italy to provide a flail mower with features not found in the light-duty bargain brands.

Features of our flail mowers include:

- Heavy-gauge steel that will stand up to abuse in tough conditions.
- Three commercial-duty belts in the drive system. "Y" blades that are heavy enough to cut through tough brush while also offering a nice cut to any lawn or pasture.
- Parking stand that keeps the flail mower in the proper position for unmounting and mounting.
- Adjustable anti-scalp shoes to protect blades and turf.
- Rear roller that sets cutting height and leaves behind an attractive stripe pattern on lawns.
- Multiple mounting points for your 3 point hitch that allow you to adjust the offset to fit your tractor's width.
- Reversible mounting capability that enables this flail mower to be assembled to operate in reverse, allowing material to be cut before it is run over by the tractor. This can be an especially handy feature when mowing down tough brush like multiflora rose and bush honeysuckle.



Pictured: (left & right) The Ibox TM73 Flail Mower, & (middle) the Ibox TX52 Flail Mower

Visit our website for more information, videos, and pricing at www.tractortoolsdirect.com.



800 S. 9th Street, Terre Haute, IN 47807
260-BALE-HAY (260-225-3429)
info@tractortoolsdirect.com

TX52 Flail Mower

DIMENSIONS AND WEIGHT

WEIGHT	540 LBS
CUTTING WIDTH	4ft 4in (52 in)
CUTTING HEIGHT	VARIABLE; 1.06 in, 1.65 in, 1.85 in

GENERAL

TYPE AND NO. OF BLADES	Y BLADES, 40
BLADE MOUNTING POINTS	20
NO. OF BELTS	3
REAR ROLLER	ADJUSTABLE; 3 POSITIONS
BELT TENSIONER	ADJUSTABLE
GREASE FIITINGS	YES

TRACTOR REQUIREMENTS

MIN. TRACTOR ENGINE POWER	20 HP
TRACTOR HITCH	CAT. 1, 3-POINT
PTO	540 RPM

TS62 Flail Mower

DIMENSIONS AND WEIGHT

WEIGHT	594 LBS
CUTTING WIDTH	5ft 2in (62 in)
CUTTING HEIGHT	VARIABLE; 1.06 in, 1.65 in, 1.85 in

GENERAL

TYPE AND NO. OF BLADES	Y BLADES, 48
BLADE MOUNTING POINTS	24
NO. OF BELTS	3
REAR ROLLER	ADJUSTABLE; 3 POSITIONS
BELT TENSIONER	ADJUSTABLE
GREASE FIITINGS	YES

TRACTOR REQUIREMENTS

MIN. TRACTOR ENGINE POWER	25 HP
TRACTOR HITCH	CAT. 1, 3-POINT
PTO	540 RPM

TM73 Flail Mower

DIMENSIONS AND WEIGHT

WEIGHT	660 LBS
CUTTING WIDTH	6ft 3in (73 in)
CUTTING HEIGHT	VARIABLE; 1.06 in, 1.65 in, 1.85 in

GENERAL

TYPE AND NO. OF BLADES	Y BLADES, 56
BLADE MOUNTING POINTS	28
NO. OF BELTS	3
REAR ROLLER	ADJUSTABLE; 3 POSITIONS
BELT TENSIONER	ADJUSTABLE
GREASE FIITINGS	YES

TRACTOR REQUIREMENTS

MIN. TRACTOR ENGINE POWER	35 HP
TRACTOR HITCH	CAT. 1, 3-POINT
PTO	540 RPM

TL84Flail Mower

DIMENSIONS AND WEIGHT

WEIGHT	826 LBS
CUTTING WIDTH	7ft 4in (84 in)
CUTTING HEIGHT	VARIABLE; 1.06 in, 1.65 in, 1.85 in

GENERAL

TYPE AND NO. OF BLADES	Y BLADES, 64
BLADE MOUNTING POINTS	32
NO. OF BELTS	3
REAR ROLLER	ADJUSTABLE; 3 POSITIONS
BELT TENSIONER	ADJUSTABLE
GREASE FIITINGS	YES

TRACTOR REQUIREMENTS

MIN. TRACTOR ENGINE POWER	45 HP
TRACTOR HITCH	CAT. 1, 3-POINT
PTO	540 RPM

V

Visit our website for more information, videos, and pricing at www.tractortoolsdirect.com.