

Flail Mowers

TX52 Flail Mower

DIMENSIONS AND WEIGHT

WEIGHT	540 LBS
CUTTING WIDTH	4ft 4in (52 in)
CUTTING HEIGHT	VARIABLE; 1.06 in, 1.65 in, 1.85 in

GENERAL

TYPE AND NO. OF BLADES	Y BLADES, 40
BLADE MOUNTING POINTS	20
NO. OF BELTS	3
REAR ROLLER	ADJUSTABLE; 3 POSITIONS
BELT TENSIONER	ADJUSTABLE
GREASE FIITINGS	YES

TRACTOR REQUIREMENTS

MIN. TRACTOR ENGINE POWER	20 HP
TRACTOR HITCH	CAT. 1, 3-POINT
PTO	540 RPM

TS62 Flail Mower

DIMENSIONS AND WEIGHT

WEIGHT	594 LBS
CUTTING WIDTH	5ft 2in (62 in)
CUTTING HEIGHT	VARIABLE; 1.06 in, 1.65 in, 1.85 in

GENERAL

TYPE AND NO. OF BLADES	Y BLADES, 48
BLADE MOUNTING POINTS	24
NO. OF BELTS	3
REAR ROLLER	ADJUSTABLE; 3 POSITIONS
BELT TENSIONER	ADJUSTABLE
GREASE FIITINGS	YES

TRACTOR REQUIREMENTS

MIN. TRACTOR ENGINE POWER	25 HP
TRACTOR HITCH	CAT. 1, 3-POINT
PTO	540 RPM

TM73 Flail Mower

DIMENSIONS AND WEIGHT

WEIGHT	660 LBS
CUTTING WIDTH	6ft 3in (73 in)
CUTTING HEIGHT	VARIABLE; 1.06 in, 1.65 in, 1.85 in

GENERAL

TYPE AND NO. OF BLADES	Y BLADES, 56
BLADE MOUNTING POINTS	28
NO. OF BELTS	3
REAR ROLLER	ADJUSTABLE; 3 POSITIONS
BELT TENSIONER	ADJUSTABLE
GREASE FIITINGS	YES

TRACTOR REQUIREMENTS

MIN. TRACTOR ENGINE POWER	35 HP
TRACTOR HITCH	CAT. 1, 3-POINT
PTO	540 RPM

TL84 Flail Mower

DIMENSIONS AND WEIGHT

WEIGHT	826 LBS
CUTTING WIDTH	7ft 4in (84 in)
CUTTING HEIGHT	VARIABLE; 1.06 in, 1.65 in, 1.85 in

GENERAL

TYPE AND NO. OF BLADES	Y BLADES, 64
BLADE MOUNTING POINTS	32
NO. OF BELTS	3
REAR ROLLER	ADJUSTABLE; 3 POSITIONS
BELT TENSIONER	ADJUSTABLE
GREASE FIITINGS	YES

TRACTOR REQUIREMENTS

MIN. TRACTOR ENGINE POWER	45 HP
TRACTOR HITCH	CAT. 1, 3-POINT
PTO	540 RPM
V	




PHONE: 833-888-IBEX
EMAIL: info@ibexequipment.com
WEBSITE: ibexequipment.com

Flail Mowers




CATEGORY 1, 3-POINT HITCH

Three attachment points on the lower pins of the 3 point hitch allow mounting on multiple sizes of Category 1 tractors.



CAN BE USED IN THE REAR-MOUNTED POSITION.

Reversible mounting capability allows the mower to operate while driving in reverse, allowing material to be cut before it is run over by the tractor. This can be especially handy feature when mowing down tough brush like multiflora rose and bush honeysuckle. The rear roller sets cutting height and leaves behind an attractive stripe pattern on lawns.



PARKING POSITION

Parking stand keeps the mower in the proper position for unmounting and mounting.



HIGH END QUALITY AT A PRICE EVERYONE CAN AFFORD

Ibex flail mowers are of high Italian engineering and manufacturing quality.

- HEAVY GAUGE ITALIAN QUALITY RAW MATERIALS
- LASER WELDED CASE
- REINFORCED UNDERBELLY
- HIGHLY DURABLE 3 POINT HITCH CONSTRUCTION
- ELEGANTLY ENGINEERED AND DESIGNED FOR MAXIMUM DURABILITY AND OUTPUT
- 3 TYPES OF QUALITY BLADE CHOICES: FINISH CUT BLADES, BRUSH CUT Y BLADES AND HEAVY DUTY HAMMER BLADES
- TOP QUALITY BEARINGS WITH GREASE-ABLE FITTINGS
- 2 HEAVY DUTY TRANSMISSION BELTS DESIGNED WITH AN ADJUSTABLE TENSIONER PULLEY
- ADJUSTABLE 3 POSITION REAR ROLLER



800 SOUTH 9TH STREET, TERRE HAUTE, IN 47807