

# LOCKNLUBE®

## GREASE COUPLER

**Locks On—Stays On—Won't Leak!**



### LOCKNLUBE® GREASE COUPLER

**GC81011**

Replace your existing coupler with a LockNLube® Grease Coupler, and end greasing frustration! 1/8" NPT thread works with all grease guns and all grease fittings. Finally, a grease coupler that really works – no hands, no mess, no wasted grease!



### LOCKNLUBE® GREASE COUPLER XL

**GC81042**

The LockNLube® Grease Coupler XL features the same locking technology as the original LockNLube® Grease Coupler, with a longer barrel – over 3.5 inches of effective reach. Perfect for greasing U-joints, harvester heads, shielded PTO shafts, and deeply recessed Zerks.

### ADDITIONAL FEATURES

- Two sizes available.
- Works on all grease fittings.
- Locks on and frees up both hands to operate your grease gun.
- Uses durable nitrile rubber seal for longevity under high pressure.

A FREE spare rebuild kit is included with every coupler (a \$9.99 value). Rebuild kits last at least 10x longer than traditional couplers and work for both Regular and XL sizes.

**Save Time, Save Money, Save Grease  
and... Save Your Machines!**



Description	Specification
Max Pressure	10,000 psi (690 Bar)
Compatibility	Fits all zerks (grease nipples)
Coupler Thread	1/8" NPT female thread
Dimensions	<b>Regular:</b> L: 3 1/2" × W: 5/8" × H: 1 7/8" L: 85 × W: 16 × H: 43 mm <b>XL:</b> L: 5 3/8" × W: 5/8" × H: 1 7/8" L: 138 × W: 16 × H: 43 mm
Diameter (front coupler)	5/8" (16 mm) Fits most recessed zerks
Weight	<b>Regular:</b> 4 oz. (100 g) <b>XL:</b> 6 oz. (165 g)

Get yours today at: [www.tractortoolsdirect.com](http://www.tractortoolsdirect.com)

LOCKING GREASE COUPLERS