

Drum Mowers

TX45 Drum Mower

DIMENSIONS AND WEIGHT

WEIGHT	453 LBS
CUTTING WIDTH	3ft 9in (45 in)

GENERAL

FOLDING FOR TRANSPORT	MANUAL
NO. OF BLADES	8(4 PER DRUM)
NO. OF DRUMS	2
MOWING CAPACITY (ACRES)	3 PER HOUR
LIFT KIT	(OPTIONAL)
BREAK AWAY PROTECTION	NO

TRACTOR REQUIREMENTS

MIN. TRACTOR ENGINE POWER	18 HP
MAX. TRACTOR ENGINE POWER	30 HP
TRACTOR HITCH	CAT. 1, 3-POINT
PTO	540 RPM
MIN. TRACTOR WIDTH	3 ft (36in)
MAX. TRACTOR WIDTH	4ft 6in (54in)
MIN. TRACTOR WEIGHT	1200 LBS

TS51C Drum Mower with Conditioner

DIMENSIONS AND WEIGHT

WEIGHT	684 lbs
CUTTING WIDTH	4ft 3in (51in)

GENERAL

FOLDING FOR TRANSPORT	MANUAL
NO. OF BLADES	6(3 PER DRUM)
NO. OF DRUMS	2
MOWING CAPACITY (ACRES)	4 PER HOUR
BREAK AWAY PROTECTION	YES

TRACTOR REQUIREMENTS

MIN. TRACTOR ENGINE POWER	20 HP
TRACTOR HITCH	CAT. 1, 3-POINT
PTO	540 RPM
MIN. TRACTOR WIDTH	4ft 4in (52in)
MAX. TRACTOR WIDTH	6 ft (72in)
MIN. TRACTOR WEIGHT	2000 LBS

TS53 Drum Mower

DIMENSIONS AND WEIGHT

WEIGHT	814 LBS
CUTTING WIDTH	4ft 5in (53 in)

GENERAL

FOLDING FOR TRANSPORT	MANUAL
NO. OF BLADES	6(3 PER DRUM)
NO. OF DRUMS	2
MOWING CAPACITY (ACRES)	4 PER HOUR
BREAK AWAY PROTECTION	YES

TRACTOR REQUIREMENTS

MIN. TRACTOR ENGINE POWER	20 HP
TRACTOR HITCH	CAT. 1, 3-POINT
PTO	540 RPM
MIN. TRACTOR WIDTH	4ft 4in (52in)
MAX. TRACTOR WIDTH	6 ft (72in)
MIN. TRACTOR WEIGHT	2000 LBS

TM67 Drum Mower

DIMENSIONS AND WEIGHT

WEIGHT	814 LBS
CUTTING WIDTH	5ft 7in (67 in)

GENERAL

FOLDING FOR TRANSPORT	MANUAL
NO. OF BLADES	8(4 PER DRUM)
NO. OF DRUMS	2
MOWING CAPACITY (ACRES)	5 PER HOUR
BREAK AWAY PROTECTION	YES

TRACTOR REQUIREMENTS

MIN. TRACTOR ENGINE POWER	32 HP
TRACTOR HITCH	CAT. 1, 3-POINT
PTO	540 RPM
MIN. TRACTOR WIDTH	4ft 6in (54in)
MAX. TRACTOR WIDTH	7 ft (84in)
MIN. TRACTOR WEIGHT	3000 LBS

TM67C Drum Mower with Conditioner

DIMENSIONS AND WEIGHT

WEIGHT	1250 LBS
CUTTING WIDTH	5ft 7in (67 in)

GENERAL

FOLDING FOR TRANSPORT	MANUAL
NO. OF BLADES	8(4 PER DRUM)
NO. OF DRUMS	2
MOWING CAPACITY (ACRES)	7 PER HOUR
BREAK AWAY PROTECTION	YES

TRACTOR REQUIREMENTS

MIN. TRACTOR ENGINE POWER	35 HP
TRACTOR HITCH	CAT. 1 OR 2, 3-POINT
PTO	540 RPM
MIN. TRACTOR WIDTH	5 ft (60in)
MAX. TRACTOR WIDTH	7 ft (84in)
MIN. TRACTOR WEIGHT	3000 LBS

TL75 Drum Mower

DIMENSIONS AND WEIGHT

WEIGHT	869 LBS
CUTTING WIDTH	6ft 3in (75 in)

GENERAL

FOLDING FOR TRANSPORT	MANUAL
NO. OF BLADES	8(4 PER DRUM)
NO. OF DRUMS	2
MOWING CAPACITY (ACRES)	7 PER HOUR
BREAK AWAY PROTECTION	YES

TRACTOR REQUIREMENTS

MIN. TRACTOR ENGINE POWER	40 HP
TRACTOR HITCH	CAT. 1 OR 2, 3-POINT
PTO	540 RPM
MIN. TRACTOR WIDTH	5 ft (60in)
MAX. TRACTOR WIDTH	7 in (84in)
MIN. TRACTOR WEIGHT	3500 LBS



PHONE: 833-888-IBEX
 EMAIL: info@ibexequipment.com
 WEBSITE: ibexequipment.com

Drum Mowers



PERFECTLY SUITED FOR SMALL-FRAMED TRACTORS.

Drum mowers are sturdy, low maintenance machines designed for compact tractors. Simple and durable, they are easy to use and will give you years of trouble free service. With 45" to 75" cutting widths and fast cutting speeds, these mowers will outperform other mower designs in the tough conditions of a hay field.



MECHANICALLY SIMPLE.

The design of a drum mower is mechanically simple. For nearly all hay cutting applications, it is a superior design that cuts faster with fewer problems. A drum mower has only two large counter-rotating drums. These drums create a great deal of inertia, helping you to power through the thickest hay conditions. These drum mowers use only four inexpensive, reversible blades per drum that are simple to replace. This simplicity in design makes IbeX Drum Mowers easy to use and maintain, while also making them extremely durable.



CONDITIONER MODELS AVAILABLE

The TS51C and TM67C mowers feature a built-in flail conditioning system that spreads the crop to reduce drying time, often eliminating the need for a separate tedder operation.

SHAFT-DRIVEN, THUS NO BELTS TO BREAK.

While other manufacturers continue to use belts between the main PTO and the drum gearbox, all of our drum mowers use a durable shaft-driven system. Shaft drive means no belts to come off, slip, or break at the most inconvenient times. Protective clutch features ensure your safety and protect your mower for years of dependable service.



GUARANTEED TO GIVE YEARS OF TROUBLE-FREE PERFORMANCE.

These machines are quality crafted in Italy, with a proven design in use for over 20 years. Every drum is factory tested to be dynamically balanced, reducing vibration and prolonging machine life. When you buy an IbeX mower, you can count on a quality machine that will give you many years of trouble-free performance.



HIGH END QUALITY AT A PRICE EVERYONE CAN AFFORD

IbeX drum mowers are of high Italian engineering and manufacturing quality.

