



TTR 4400 HST



Hydrostatic and Reversible

More tractor for the money - and many machines in one. The TTR 4400 HST machines are hydrostatic, reversible and multifunctional. The machine-attachment combination is almost endless, performing a wide range of operations: maintaining parks, manicuring golf courses, cutting grass on roadway edges and the steepest of slopes, moving material and digging, and clearing snow, to name a few. To call it just a tractor undersells its capabilities - it is truly a multifunctional tool carrier.

The speed and agility of the TTR 4400 HST, its exceptional steering, compact dimensions, and low-noise operation, make this a perfect machine for the public sector. No other machine can provide the productivity, safety, and maneuverability to perform property management tasks all year around.



Visit our website for more information, videos, and pricing at www.tractortoolsdirect.com.



800 S. 9th Street, Terre Haute, IN 47807 260-BALE-HAY (260-225-3429) info@tractortoolsdirect.com

SPECIFICATIONS:

Chassis type Oscillating chassis with front steering;

4 equal wheel drive; reversible operator's station

Engine Yanmar TNV88

Cylinders 3
Output (hp) 38
Max. engine RPM 3000
Cooling System Water
Fuel tank capacity (gal.) 7.7

Transmisssion 3 range hydrostatic, foot controlled toe/heel forward and reverse; 0-4 mph in

low range, 0-8 mph in normal range, 0-17 mph in high range; "cruise control"

option for maintaining pre-set speed

PTO Fully independent PTO with 2 speeds, 540 and 1000 rpm (clockwise)

Implement lift Standard Category one 3 point hitch

Lifting capacity (lbs.) 1870

Steering Hydrostatic with "load sensing" system

Tires 7.5-16 29x12.5-15 turf 29x12.5-15 lug 26.5x14.5-12 special turf

Minimum width (in.) 46 54 59 Ground clearance (in.) 10.8 10 10 8.7

Weight (lbs.) 2450

Standard equipment Rotating operators station for immediate reversibility of driving position; front

and rear differential lock; disengageable rear wheel drive; adjustable suspension

seat; 2 sets of hydraulic ports with one set duplicated on front of tractor

 Wheelbase (in.)
 51.2

 Length (in.)
 122

 Height (in.)
 78.2-80



Visit our website for more information, videos, and pricing at www.tractortoolsdirect.com.